

Unterputzbohrschablone 82 mm 5-Fach



- ❖ Ergänzt das Therm Dosen System
- ❖ Für Ytong, Ziegel, Kalksandstein und andere Mauerwerke
- ❖ Bohrloch nur einmal einmessen
- ❖ Für gerade und präzise Bohrlöcher
- ❖ Schnellspannfunktion
- ❖ Zwei integrierte Wasserwaagen
- ❖ Für 5-fach Kombinationen geeignet

| | |
|---------------|---------------|
| Artikelnummer | P718-05 |
| Kategorie | Werkzeuge |
| Montageart | - |
| EAN | 4260182067352 |
| Material | Edelstahl V2A |
| Farbe | grau |

Produkteigenschaften

| | |
|------------------------|--------|
| Durchmesser | 82 mm |
| Länge | 410 mm |
| Breite | 130 mm |
| Höhe Führungshülsen | 49 mm |
| Höhe Spanngummi | 50 mm |
| Durchmesser Spanngummi | 81 mm |

Flush-mounted drilling template 82 mm 5-fold



- ❖ Complements the Thermo box system
- ❖ For Ytong, brick, sand-lime brick and other masonry materials
- ❖ Measure the drill hole only once
- ❖ For straight and precise drill holes
- ❖ Quick clamping function
- ❖ Two integrated spirit levels
- ❖ Suitable for 5-fold combinations

| | |
|----------------------|---------------------|
| Article No. | P718-05 |
| Category | Tools |
| Type of installation | - |
| EAN | 4260182067352 |
| Material case | Stainless steel V2A |
| Colour | gray |

Product features

| | |
|-----------------------------|--------|
| Diameter | 82 mm |
| Length | 410 mm |
| Width | 130 mm |
| Height of guide sleeves | 49 mm |
| Height of clamping rubber | 50 mm |
| Diameter of clamping rubber | 81 mm |